

TED TODD

SPECIFICATION SHEET

HUSK NARROW

Item code: WAREBL09 Collection: Warehouse

Overview		
Wood Species	European Oak	
Design	Herringbone	
Grade	Nature	
Profile	Groove to three sides	
Edge Detail	Micro bevelled	
Construction	2 Ply Engineered - 100% Hardwood	
Wear Layer	4mm Hardwood (Nominal)	
Application Guide	Floors & walls	
Dimensions		
Width	90mm	
Thickness	15mm	
Length	450mm	
Tolerance	+/- 0.25mm / 95% in tolerance	
Pack Size, M2	1.296 m2 - order to the nearest pack size	
Finish		
Finish	Hardened Oil	
Surface Texture	Undulating texture	
Tone	Mid Tone	
Tonal Variation	Medium natural tonal variation	
Batch Variation	Not advised to mix batches in one floor area	
Handover guidance	Fully finished, ready for use.	
Floor Care	Care System 1	
Environmental Certification		
Certification	FSC 100% - independently audited, since 1997, chain of custody tracking	
EUTR Compliant	Yes	
Installation Guidelines		
Floating Installation	Yes - Ted Todd Universal bond	
Secret Nail	No	



Structural FloorNoFully BondYes - Ted Todd MS Flex high strength adhesiveSub floor PrimerYes - Ted Todd PrimerfastUnderfloor HeatingYes - please see usage guidelinesSub FloorsDry, FlatConcreteDry, FlatPlywoodYesScreedDry, flat, with Primerfast moisture barrierFormed Tread + RiserYes - 7 day serviceSkirting, ArchitraveYes by requestTechnical InformationS-12% fair and average moisure contentSlip RatingEflStating FlooringEflEN 13501-1 Fire Rating FlooringSetween 40 and 60% relative humidityPriguirements1,120 lbf (4980N)OriginEuropeanJanka Hardness Rating1,120 lbf (4980N)Shipment timesLargest UK Stocks - available 3 day servicePinemal ConductivitStorm 0.08m2K/W, 0.8 TogShipment times20 year product warrantyLife SpanGenerational life span if cared forRuantee20 year product warrantyLife SpanSenvering into upscale uses, worst			
adhesiveSub floor PrimerYes - Ted Todd PrimerfastUnderfloor HeatingYes - please see usage guidelinesSub FloorsDry, FlatConcreteDry, FlatPlywoodYesScreedDry, flat, with Primerfast moisture barrierFormed Tread + RiserYes - Made to order - 14 day serviceL Section, T Section, Reducer, ScotiaYes - 7 day serviceSkirting, ArchitraveYes by requestTechnical Information8-12% fair and average moisure contentSlip RatingLow risk dry. Moderate risk wet.EN 13501-1 Fire Rating FlooringEflEN 14342 EmissionsE1Humidity requirementsBetween 40 and 60% relative humidityOriginEuropeanJanka Hardness Rating1,120 lbf (4980N)RatingPalletised, wrapped + bandedShipping InformationE1Shipping In	Structural Floor	No	
Underfloor HeatingYes - please see usage guidelinesSub FloorsConcreteDry, FlatPlywoodYesScreedDry, flat, with Primerfast moisture barrierFormed Tread + RiserYes - Made to order - 14 day serviceL Section, T Section, Reducer, ScotiaYes - 7 day serviceSkirting, ArchitraveYes by requestTechnical Information8-12% fair and average moisure contentSlip RatingLow risk dry. Moderate risk wet.Slip RatingE1EN 13501-1 Fire Rating FlooringBetween 40 and 60% relative humidity requirementsOriginEuropeanJanka Hardness Rating1,120 lbf (4980N)Formaldehyde EmissionE1Shipping InformationLargest UK Stocks - available 3 day servicePackagingPalletised, wrapped + bandedGuarantee20 year product warrantyLife CycleLife SpanLife SpanGenerational life span if cared forRecycleValue in recycling into upscale uses, worst	Fully Bond	o o	
Sub FloorsConcreteDry, FlatPlywoodYesScreedDry, flat, with Primerfast moisture barrierFormed Tread + RiserYes - Made to order - 14 day serviceL Section, T Section, Reducer, ScotiaYes - 7 day serviceSkirting, ArchitraveYes by requestTechnical Information8-12% fair and average moisure contentSlip RatingLow risk dry. Moderate risk wet.EN 14342 EmissionsEflRating FlooringEflVorginEuropeanJanka Hardness Rating1,120 lbf (4980N)RatingEflShipping InformationEflShipping InformationEflShipping InformationEflStatting2.0 year product warrantyLierequirements0.0 service for available 3 day servicePormaldehyde Emission2.0 year product warrantyLife CycleUaue in recycling into upscale uses, worst	Sub floor Primer	Yes - Ted Todd Primerfast	
ConcreteDry, FlatPlywoodYesScreedDry, flat, with Primerfast moisture barrierFormed Tread + RiserYes - Made to order - 14 day serviceL Section, T Section, Reducer, ScotiaYes - 7 day serviceSkirting, ArchitraveYes by requestTechnical Information8-12% fair and average moisure contentSlip RatingLow risk dry. Moderate risk wet.EN 13501-1 Fire Rating FlooringEflEN 14342 EmissionsE1Humidity requirementsBetween 40 and 60% relative humidity requirementsOriginEuropeanJanka Hardness Rating1,120 lbf (4980N) RatingFormaldehyde E1E1EmissionE1Shipping InformationLargest UK Stocks - available 3 day servicePackagingPalletised, wrapped + bandedGuarantee20 year product warrantyLife CycleLife SpanLife SpanGenerational life span if cared forRecycleValue in recycling into upscale uses, worst	Underfloor Heating	Yes - please see usage guidelines	
PlywoodYesScreedDry, flat, with Primerfast moisture barrierFormed Tread + RiserYes - Made to order - 14 day serviceI Section, T Section, Reducer, ScotiaYes - 7 day serviceSkirting, ArchitraveYes by requestTechnical Information8-12% fair and average moisure contentSlip RatingLow risk dry. Moderate risk wet.EN 13501-1 Fire Rating FlooringEflEN 14342 EmissionsE1Humidity requirementsBetween 40 and 60% relative humidity requirementsOriginEuropeanJanka Hardness Rating1,120 lbf (4980N) RatingFormaldehyde EnsisionE1Shipping InformationLargest UK Stocks - available 3 day servicePackagingPalletised, wrapped + bandedGuarantee20 year product warrantyLife CycleValue in recycling into upscale uses, worst	Sub Floors		
ScreedDry, flat, with Primerfast moisture barrierFormed Tread + RiserYes - Made to order - 14 day serviceFormed Tread + RiserYes - 7 day serviceL Section, T Section, Reducer, ScotiaYes by requestTechnical InformationYes by requestTechnical Information8-12% fair and average moisure contentSlip RatingLow risk dry. Moderate risk wet.EN 13501-1 Fire Rating FlooringEflEN 14342 EmissionsE1Humidity requirementsBetween 40 and 60% relative humidityOriginEuropeanJanka Hardness Rating1,120 lbf (4980N)RatingE1Shipping InformationE1Shipping InformationE1Shipping InformationE1Stargest UK Stocks - available 3 day servicePaletised, wrapped + bandedGuarantee20 year product warrantyLife CycleLife SpanLife SpanGenerational life span if cared forRecycleValue in recycling into upscale uses, worst	Concrete	Dry, Flat	
Formed Tread + RiserYes - Made to order - 14 day service Reducer, ScotiaL Section, T Section, Reducer, ScotiaYes - 7 day service ServiceSkirting, ArchitraveYes by requestTechnical Informatio8-12% fair and average moisure contentSlip RatingLow risk dry. Moderate risk wet.EIn 13501-1 Fire Rating FlooringEflEN 14342 EmissionsE1Humidity requirementsBetween 40 and 60% relative humidity requirementsOriginEuropeanJanka Hardness Rating1,120 lbf (4980N) RatingFormaldehyde EmissionE1Shipping InformationStorm 0.08m2K/W, 0.8 TogShipping InformationLargest UK Stocks - available 3 day service Paletised, wrapped + bandedGuarantee20 year product warrantyLife CycleLife SpanLife SpanGenerational life span if cared for RecycleKaley Value in recycling into upscale uses, worst	Plywood	Yes	
RiserL Section, T Section, Reducer, ScotiaYes - 7 day service Reducer, ScotiaSkirting, ArchitraveYes by requestTechnical Information8-12% fair and average moisure contentMoisture Content8-12% fair and average moisure contentSlip RatingLow risk dry. Moderate risk wet.EN 13501-1 Fire Rating FlooringEflEN 14342 EmissionsE1Humidity requirementsBetween 40 and 60% relative humidity requirementsOriginEuropeanJanka Hardness Rating1,120 lbf (4980N) RatingFormaldehyde EnssionE1Shipping Information15mm 0.08m2K/W, 0.8 TogShipment timesLargest UK Stocks - available 3 day servicePackagingPalletised, wrapped + bandedGuarantee20 year product warrantyLife CycleLife SpanLife SpanGenerational life span if cared forRecycleValue in recycling into upscale uses, worst	Screed	Dry, flat, with Primerfast moisture barrier	
Reducer, ScotiaYes by requestSkirting, ArchitraveYes by requestTechnical Information8-12% fair and average moisure contentSlip RatingLow risk dry. Moderate risk wet.EN 13501-1 Fire Rating FlooringEflEN 14342 EmissionsE1Humidity requirementsBetween 40 and 60% relative humidityOriginEuropeanJanka Hardness Rating1,120 lbf (4980N)RatingE1Formaldehyde EmissionE1Thermal Conductivity15mm 0.08m2K/W, 0.8 TogShipping InformationLargest UK Stocks - available 3 day servicePackagingPalletised, wrapped + bandedGuarantee20 year product warrantyLife CycleSenerational life span if cared forRecycleValue in recycling into upscale uses, worst		Yes - Made to order - 14 day service	
Technical InformationMoisture Content8-12% fair and average moisure contentSlip RatingLow risk dry. Moderate risk wet.EN 13501-1 Fire Rating FlooringEflEN 14342 EmissionsE1Humidity requirementsBetween 40 and 60% relative humidityOriginEuropeanJanka Hardness Rating1,120 lbf (4980N)RatingE1Formaldehyde EmissionE1Thermal Conductivity15mm 0.08m2K/W, 0.8 TogShipping InformationLargest UK Stocks - available 3 day servicePackagingPalletised, wrapped + bandedGuarantee20 year product warrantyLife CycleEnerational life span if cared forRecycleValue in recycling into upscale uses, worst		Yes - 7 day service	
Non-transmissionMoisture Content8-12% fair and average moisure contentSlip RatingLow risk dry. Moderate risk wet.EN 13501-1 Fire Rating FlooringEflEN 14342 EmissionsE1Humidity requirementsBetween 40 and 60% relative humidityOriginEuropeanJanka Hardness Rating1,120 lbf (4980N)Formaldehyde EnssionE1Thermal Conductivity15mm 0.08m2K/W, 0.8 TogShipping InformationLargest UK Stocks - available 3 day servicePackagingPalletised, wrapped + bandedGuarantee20 year product warrantyLife CycleLife SpanGenerational life span if cared forRecycleValue in recycling into upscale uses, worst	Skirting, Architrave	Yes by request	
Slip RatingLow risk dry. Moderate risk wet.EN 13501-1 Fire Rating FlooringEflEN 14342 EmissionsE1Humidity requirementsBetween 40 and 60% relative humidity requirementsOriginEuropeanJanka Hardness Rating1,120 lbf (4980N) RatingFormaldehyde EmissionE1Thermal Conductivity15mm 0.08m2K/W, 0.8 TogShipping InformationLargest UK Stocks - available 3 day servicePackagingPalletised, wrapped + bandedGuarantee20 year product warrantyLife CycleEnerational life span if cared forRecycleValue in recycling into upscale uses, worst	Technical Information		
EN 13501-1 Fire Rating FlooringEflEN 14342 EmissionsE1Humidity requirementsBetween 40 and 60% relative humidityOriginEuropeanJanka Hardness Rating1,120 lbf (4980N)Formaldehyde EnissionE1Formaldehyde EnissionE1Shipping Information15mm 0.08m2K/W, 0.8 TogShipping InformationLargest UK Stocks - available 3 day servicePackagingPalletised, wrapped + bandedGuarantee20 year product warrantyLife CycleEnerational life span if cared forRecycleValue in recycling into upscale uses, worst	Moisture Content	8-12% fair and average moisure content	
Rating FlooringEN 14342 EmissionsE1Humidity requirementsBetween 40 and 60% relative humidityOriginEuropeanJanka Hardness Rating1,120 lbf (4980N)Formaldehyde EmissionE1FormalConductivity15mm 0.08m2K/W, 0.8 TogShipping InformationLargest UK Stocks - available 3 day servicePackagingPalletised, wrapped + bandedGuarantee20 year product warrantyLife CycleLife SpanRecycleValue in recycling into upscale uses, worst	Slip Rating	Low risk dry. Moderate risk wet.	
Humidity requirementsBetween 40 and 60% relative humidityOriginEuropeanJanka Hardness Rating1,120 lbf (4980N)Formaldehyde EmissionE1Formaldenyde Emission15mm 0.08m2K/W, 0.8 TogShipping InformationJomm 0.08m2K/W, 0.8 TogShippent timesLargest UK Stocks - available 3 day servicePackagingPalletised, wrapped + bandedGuarantee20 year product warrantyLife CycleLife SpanLife SpanGenerational life span if cared forRecycleValue in recycling into upscale uses, worst		Efl	
requirementsOriginEuropeanJanka Hardness Rating1,120 lbf (4980N)Formaldehyde EmissionE1Formaldenyde EmissionE1Thermal Conductivity15mm 0.08m2K/W, 0.8 TogShipping InformationLargest UK Stocks - available 3 day servicePackagingPalletised, wrapped + bandedGuarantee20 year product warrantyLife CycleLife SpanRecycleValue in recycling into upscale uses, worst	EN 14342 Emissions	E1	
Janka Hardness Rating1,120 lbf (4980N)RatingE1Formaldehyde EmissionE1Thermal Conductivity15mm 0.08m2K/W, 0.8 TogShipping InformationLargest UK Stocks - available 3 day servicePackagingPalletised, wrapped + bandedPackagingPalletised, wrapped + bandedGuarantee20 year product warrantyLife CycleLife SpanLife SpanGenerational life span if cared forRecycleValue in recycling into upscale uses, worst	2	Between 40 and 60% relative humidity	
RatingFormaldehyde EmissionE1Thermal Conductivity15mm 0.08m2K/W, 0.8 TogShipping Information15mm 0.08m2K/W, 0.8 TogShipping InformationLargest UK Stocks - available 3 day servicePackagingPalletised, wrapped + bandedPackagingPalletised, wrapped + bandedGuarantee20 year product warrantyLife CycleLife SpanLife SpanGenerational life span if cared forRecycleValue in recycling into upscale uses, worst	Origin	European	
EmissionEmissionThermal Conductivity15mm 0.08m2K/W, 0.8 TogShipping InformationShipment timesLargest UK Stocks - available 3 day servicePackagingPalletised, wrapped + bandedGuarantee20 year product warrantyLife CycleLife SpanLife SpanGenerational life span if cared forRecycleValue in recycling into upscale uses, worst		1,120 lbf (4980N)	
Shipping InformationShipping InformationShipment timesLargest UK Stocks - available 3 day servicePackagingPalletised, wrapped + bandedGuarantee20 year product warrantyLife CycleLife SpanLife SpanGenerational life span if cared forRecycleValue in recycling into upscale uses, worst		E1	
Shipment timesLargest UK Stocks - available 3 day servicePackagingPalletised, wrapped + bandedGuarantee20 year product warrantyLife CycleLife SpanLife SpanGenerational life span if cared forRecycleValue in recycling into upscale uses, worst	Thermal Conductivity	15mm 0.08m2K/W, 0.8 Tog	
PackagingPalletised, wrapped + bandedGuarantee20 year product warrantyGuarantee20 year product warrantyLife CycleLife SpanLife SpanGenerational life span if cared forRecycleValue in recycling into upscale uses, worst	Shipping Information		
Guarantee 20 year product warranty Life Cycle Eife Span Life Span Generational life span if cared for Recycle Value in recycling into upscale uses, worst	Shipment times	Largest UK Stocks - available 3 day service	
Guarantee 20 year product warranty Life Cycle Eife Span Life Span Generational life span if cared for Recycle Value in recycling into upscale uses, worst	Packaging	Palletised, wrapped + banded	
Life Cycle Life Span Generational life span if cared for Recycle Value in recycling into upscale uses, worst	Guarantee		
Life SpanGenerational life span if cared forRecycleValue in recycling into upscale uses, worst	Guarantee	20 year product warranty	
Recycle Value in recycling into upscale uses, worst	Life Cycle		
	Life Span	Generational life span if cared for	
	Recycle		





18 Chesford Grange, Woolston, Warrington, Cheshire, WA1 4RQ | Tel: 01925 283000 | Fax: 01925 283001 | www.tedtodd.co.uk | Company Registration No: 2848796 | VAT Registration No: 719682205